## Prestige PUR | Pearlazzo PUR

High performance, heavy duty homogeneous floor coverings with a polyurethane reinforcement for low cost, lifetime polish free maintenance. Prestige PUR features a non-directional duotone decoration, with tonal highlight chips and Pearlazzo PUR features a unique decoration comprising a blend of tonal chips and pearlescent flakes. Achieving BRE Global Environment A+ Rating (ENP 472) in major sectors such as health, education and retail, Prestige and Pearlazzo are 100% recyclable and contain 25% recycled material.



Gauge	ISO 24346 (EN 428)	2.0mm
Roll Size	ISO 24341 (EN 426)	2m x 20m = 40m <sup>2</sup>
Total Weight	ISO 23997 (EN 430)	2950/m <sup>2</sup>
General Performance	EN ISO 10581 (EN 649) ASTM F1913	Conforms Class I, Type A
Use Area	ISO 10874 (EN 685)	
	EN 13501-1	Class BfI-S1
	ASTM E662	<450
Reaction to Fire	ASTM E648	Class 1
	CAN/ULC S102.2	FSV < 300; SDV < 500
	AS ISO 9239-1	>8.0 kW/m <sup>2</sup>
Abrasion Resistance	EN 660-2	Group T
Binder Content	EN ISO 10581	Туре I
	EN 13893	Class DS
	DIN 51130 /	R9
Slip Resistance	DIN EN 16165 Ann. B	
· · · · · · · · ·	AS 4586	R9
	ASTM D2047	SCOF >0.6
	ASTM F970 (Modified)	≤0.005" (750 psi)
Residual Indentation	ISO 24343-1 (EN 433)	≤0.10mm
Impact Sound Reduction	EN ISO 10140-3	4dB
Static Electrical Propensity	EN 1815	≤2.0kV Classified as 'antistatic'
	ISO 26987 (EN 423)	Good
Resistance to Chemicals	ASTM F925	Good
Light Fastness	ISO 105-B02	≥6
Castor Chair (continuous use)	ISO 4918 (EN 425)	Suitable
Flexibility	ASTM F137	Pass
	Indoor Air Comfort GOLD	Eurofins certified product
VOC Emissions	AgBB/ABG	Pass
	FloorScore	Certified
	Finnish M1 Classification	Certified
	TVOC after 28 days	≤ 10µg/m <sup>3</sup>
Responsible Sourcing	BES 6001	Excellent
	220 000.	

PUR and Pearlazzo PUR are 100% recyclable and contain 25% recycled material. Recyclable via the Recofloor scheme. Visit www.polyflor.com/sustainability.

PUR - Prestige PUR and Pearlazzo PUR features a high quality, cross-linked polyurethane reinforcement, UV cured to provide a low-cost, polish free maintenance regime for the lifetime of the flooring.

	Bacterial Resistance	ISO 846 Part C	Does not favour growth
	Ease of Radioactive Decontamination	ISO 8690	Excellent
	Hygiene - All Polyflor commercial sheet vinyl ranges provide a continuous, impervious and hygienic flooring solution which can be confidently cleaned in accordance with recommended maintenance procedures and approved maintenance products. The implementation of an effective cleaning regime is the mos		

\$

important defence against infection. Agrément Assurance - Prestige PUR and Pearlazzo PUR have been independently assessed by the British Board of Agrément and product performance is assured for at least 10 years in recommended use areas. With proper maintenance, the appearance and colour will be retained during this period. Polyflor homogeneous PUR ranges are compatible for use with the most commonly used alco-based hand gels and are suitable for steam cleaning on a

periodic basis. For information regarding handling and installation, adhesives, maintenance, applications and product warranty, consult Polyflor Customer Technical Services on +44 (0)161 767 1912, or email tech@polyflor.com. The data presented is correct at the time of printing. For latest information, please visit our website polyflor.com.

Decoration and shade may vary slightly from the samples shown.









UK sales: +44 (0)161 767 1122 Export sales: +44 (0)161 767 1913 Samples: +44 (0)161767 2551 email: info@polyflor.com www.polyflor.com

