

# Polysafe™ QuickLay PUR

A loose lay safety flooring designed for adhesive free installation, Polysafe QuickLay can be laid over a variety of existing subfloors including new concrete substrates of up to 97% RH. Reduced subfloor preparation requirements & quicker installation makes Polysafe QuickLay the perfect solution for quick turnaround projects in areas where slip resistance is the priority. Typical areas include circulation areas & corridors, classrooms, hospital wards, clinics, nursing homes, washrooms, bar serveries, food preparation areas, canteens & institutional applications. For continually wet areas please refer to our Polysafe Hydro, Hydro Evolve or Quattro ranges.



	<b>Gauge</b>	ISO 24346 (EN 428)	2.2mm
	<b>Roll Size</b>	ISO 24341 (EN 426)	2m x 20m = 40m <sup>2</sup>
	<b>Total Weight</b>	ISO 23997 (EN 430)	2700g/m <sup>2</sup>
	<b>General Performance</b>	EN 13845 ASTM F1303	Conforms Conforms
	<b>Use Area</b>	ISO 10874 (EN 685)	
	<b>Enhanced Slip Resistance</b>	EN 13845 AS 4586 Appendix A AS 4586 Appendix D DIN 51130/DIN EN 16165 Ann. B RRL Pendulum Test Surface Roughness ASTM D2047	ESf P4 R11 R11 ≥45 (wet test - 4S Rubber/Slider 96) Rz ≥20µm SCOF ≥0.8
<b>The wet slip resistance across all Polysafe products is sustainable throughout the guaranteed life of the product, with strict adherence to HSE Guidelines. For further clarification regarding slip resistance, consult Polyflor.</b>			
	<b>Abrasion Resistance</b>	EN 13845	50,000 cycles
	<b>Reaction to Fire</b>	EN 13501-1 ASTM E648 Australian BCA Spec C1.10-3 AS ISO 9239-1 CAN/ULC S 102.2	Class Bfl-S1 Class 1 Complies >8.0kW/m <sup>2</sup> FSV <300; SDV <500
	<b>Static Electrical Propensity</b>	EN 1815	≤2.0kV Classified as 'antistatic'
	<b>VOC Emissions</b>	Indoor Air Comfort GOLD AgBB/ABG FloorScore Finnish MI Classification	Eurofins certified product Pass Certified Certified
	<b>Resistance to Chemicals</b>	ISO 26987 (EN 423)	Good chemical resistance
	<b>Castor Chair Abrasion</b>	ISO 4918 (EN 425)	Suitable
	<b>Acoustic Impact Sound Reduction</b>	EN ISO 10140-3	10dB
	<b>Residual Indentation</b>	ISO 24343-1 (EN 433)	≤0.10mm
	<b>Bacterial Resistance</b>	ISO 846 Part C	Does not favour growth
<b>Environmentally Preferable Flooring</b> - Polysafe QuickLay PUR achieves BRE Global A+ rating (Generic) in the Green Guide to Specification in use areas such as education and healthcare. EN 15804 Environmental Product Declaration (EPD) available on request. It is 100% recyclable and contains recycled material. Recyclable via the Recofloor scheme. Visit <a href="http://www.polyflor.com/sustainability">www.polyflor.com/sustainability</a>			
<b>Polysafe PUR</b> - Polysafe QuickLay PUR features a high quality, cross-linked polyurethane reinforcement, UV cured to provide superior cleaning benefits, life cycle maintenance savings and optimum appearance retention. As with all Polysafe products, Polysafe QuickLay PUR should not have a polish applied.			
	<b>Hygiene</b> - All Polyflor commercial sheet vinyl ranges provide a continuous, impervious and hygienic flooring solution which can be confidently cleaned in accordance with recommended maintenance procedures and approved maintenance products. The implementation of an effective cleaning regime is the most important defence against infection.		
	Polysafe safety flooring ranges have good resistance to dilute acids and alkalis, are compatible for use with the most commonly used alcho-based hand gels and are suitable for steam cleaning on a periodic basis. Chemical resistance charts available on request. For information regarding handling and installation, adhesives, maintenance, applications, chemical resistance and product warranty, consult <b>Polyflor Customer Technical Services</b> on +44 (0)161 767 1912, or email <a href="mailto:tech@polyflor.com">tech@polyflor.com</a> .		
The data presented is correct at the time of printing. For latest information, please visit our website <a href="http://polyflor.com">polyflor.com</a> . Decoration and shade may vary slightly from the samples shown.			



**Polyflor UK** Sales Direct: +44 (0)161 767 1122 • Export Sales Direct: +44 (0)161 767 1913  
Sample Requests: +44 (0)161 767 2551 • email: [info@polyflor.com](mailto:info@polyflor.com) • [www.polyflor.com](http://www.polyflor.com)

**Polyflor Australia** Tel: 1800 777 425 • email: [sales@polyflor.com.au](mailto:sales@polyflor.com.au) • [www.polyflor.com.au](http://www.polyflor.com.au)  
**Polyflor New Zealand** Tel: 0800 765 935 • email: [sales@polyflor.co.nz](mailto:sales@polyflor.co.nz) • [www.polyflor.co.nz](http://www.polyflor.co.nz)

