

Finesse SD

PRODUCT SPECIFICATION

Key Features

- > Homogeneous sheet & tile in non-directional colour ways
- > Static Dissipative [SD] properties for static control
- > Excellent abrasion & chemical resistance
- > Weld to create an impervious floor
- > Use with Polyflor approved conductive polishes



Product Format	Standard	Result
Gauge	ISO 24346 (EN 428)	2.0mm
Total Weight	ISO 23997 (EN 430)	3030g/m ²

Sheet & Tile Sizes	Size	Shades	Quantity per Box	Coverage per Box/Roll
Sheet	2m x 20m	5	-	40m ²
Tile	608mm x 608mm	5	14	5.17m ²

Performance Requirements	Standard	Result
General Performance	ISO 10581	Conforms
	ASTM F1913	Conforms
	ASTM F1700	Conforms
Use Area	ISO 10874	34, 43
Slip Resistance	DIN 51130 / DIN EN 16165 Ann. B EN 13893	R9 Class DS
Binder Content	ISO 10581	Type I
Abrasion Resistance	EN 660-2	Group P
Reaction to Fire	EN 13501-1	Class Bfl-S1
	ASTM E648	Class 1
	ASTM E662	<450
	CAN/ULC S102.2	FSV < 300; SDV < 500
	AS ISO 9239-1	<8.0 kW/m ²
Static Electrical Propensity	EN 1815	≤2.0kV Classified as 'antistatic'
Electrical Resistance	EN 1081 R ₁ /R ₂	1.0 x 10 ⁶ - 1.0 x 10 ⁹ ohms
	ESD S 7.1	1.0 x 10 ⁶ - 1.0 x 10 ⁹ ohms
	IEC 61340-4-1	1.0 x 10 ⁶ - 1.0 x 10 ⁹ ohms
	All products require minimum 40% RH	

Sustainability	Standard	Result
BRE Green Guide		A+ Generic

Generic EN 15804 EPD	Available
Recyclable	100%
Recycled Content	25%
REACH	Compliant
Indoor Air Comfort Gold	Eurofins certified product
FloorScore	Certified
Finnish M1 Classification	Certified

Maintenance Performance

Standard

Result

Resistance to Chemicals	ISO 26987 (EN 423)	Good resistance
-------------------------	--------------------	-----------------

All Polyflor commercial sheet vinyl ranges provide a continuous, impervious and hygienic flooring solution which can be confidently cleaned in accordance with recommended maintenance procedures and approved maintenance products. The implementation of an effective cleaning regime is the most important defence against infection.

Hygiene

Standard

Result

Bacterial Resistance	ISO 846 Part C	Does not favour growth
----------------------	----------------	------------------------



Polyflor Ltd. Head Office


PO Box 3, Radcliffe New Road, Whitefield, Manchester, M45 7NR • Tel: +44 (0) 161 767 1111 • Email: info@polyflor.com • www.polyflor.com

© At the time of writing and publication of sheet, all the information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties.


Finesse SD




RANGE SHADES




Moonscape 5860 w/r 5260
NCS S 2005-Y40R LRV 55




Daybreak 5820 w/r 3130
NCS S 2500-N LRV 49



Lodestone 5830 w/r 3140
NCS S 4000-N LRV 33



Cascade 5800 w/r 5200
NCS S 3010-R80B LRV 38



Woodglade 5840 w/r 5240
NCS S 3005-G20Y LRV 41

w/r - Weld Rod

LRV - Light Reflectance Value

NCS - Natural Colour System

Polyflor Ltd. Head Office

PO Box 3, Radcliffe New Road, Whitefield, Manchester, M45 7NR • Tel: +44 (0) 161 767 1111 • Email: info@polyflor.com • www.polyflor.com

© At the time of writing and publication of sheet, all the information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties.