



Tough heavy contract, secondary entrance matting



Vulcan



Victor



Viscount



Vixen

WORKSPACE ENTRANCE

Description:

Tough heavy contract, secondary entrance matting.

All products conform to BS8300.

Low LRV Values compared to aluminium, LVL and fibrebonded products ensuring a positive point difference is easy to achieve for areas where partially sighted traffic will be important to consider.

Equalities Act 2010 compliant.

Entrance matting resistant to point loading and scuffing from rubber wheels and walking aids.

Flame properties:

Cfl-s1 for tiles

Colours:

Colour options available 4

Technical data:

Style	Tufted cut pile with integral scraper system
Fibre construction	100% solution dyed nylon
Tuft gauge	1/10"
Pile yarn weight	1,000 gsm
Pile height	5 mm +/- 0.5 mm
Pile density	114,260 tufts per square metre
Total weight	Tile 4,800 gsm / Sheet 1,800 gsm
Sheet thickness	Tile 9 mm / Sheet 8 mm
Backing	Bitumen compound / Eco-Bac / Unitary Bac
Dimensions	50 cm x 50 cm tile / 2 m x 20 m nominal
Wear classification	Heavy contract class 33
Colour fastness	To water - 5 To light - 5 To rubbing - 4.5
Flammability	Cfl-s1
Warranty	10 years